LPG SERIES-GEL BATTERY

LPG12-70H (12V70Ah)

LEOCH BATTERY





CHARACTERISTICS

Item		Specifications
Rated Voltage		12V
Nominal Capacity (25˚C)	C_{20},1.80V/cell	70Ah
Dimension	Length	260mm (10.2inches)
	Width	168mm (6.61inches)
	Container Height	208mm (8.19inches)
	Total Height	214mm (8.43inches)
Approx Weight		22.9kg (50.5lbs)
Terminal		T6(M6)
Container Material		ABS (UL94 HB or V-0 optional)
Short-circuit current		1470A
Internal Resistance (25˚C)		Approx 9.4 mΩ (Fully charged)
Operating Temp. Range	Discharge	-20~60˚C (-4~140°F)
	Charge	-20~40˚C (-4~104°F)
	Storage	-20~50˚C (-4~122°F)
Nominal Operating Temp. Range		25±3˚C (77±5°F)
Max.Charging Current (25˚C)		0.25C
Charge voltage (25˚C)	Standby Use	Cycle Use
	2.23-2.27V/cell	2.35-2.40V/cell
Temp. Coeffcient	-3mV/cell/˚C	-5mV/cell/˚C
Effect of temp. to Capacity	40˚C (104°F)	103%
	25˚C (77°F)	100%
	0˚C (32°F)	86%
Self Discharge	⩽2.5% per month at 25°C (77°F). LPG series batteries may be stored up to 9 months at 25°C (77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	

DISCHARGE TABLE

Constant Current Discharge (Amperes) at 25°C (77°F)															
F.V/Time	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	92.1	79.9	62.8	50.4	40.1	34.6	26.3	21.3	16.2	13.0	10.9	9.45	7.65	6.37	3.56
1.80V/cell	104.6	90.5	71.0	58.5	45.5	38.5	28.9	23.2	17.5	13.9	11.7	10.1	8.14	7.00	3.75
1.75V/cell	113.4	98.0	76.7	61.2	47.2	40.1	30.1	24.1	18.1	14.3	12.0	10.3	8.29	7.02	3.79
1.70V/cell	118.6	102.9	80.7	64.0	49.0	41.6	31.2	24.9	18.6	14.8	12.3	10.6	8.40	7.03	3.84
1.67V/cell	124.7	107.1	83.5	65.8	49.9	42.4	31.8	25.4	18.9	15.0	12.5	10.7	8.47	7.09	3.87
1.60V/cell	129.0	110.4	85.7	69.8	52.4	44.5	33.3	26.6	19.8	15.6	13.0	11.1	8.63	7.16	3.94

Constant Power Discharge (Watts/cell) at 25°C (77°F)															
F.V/Time	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	173.3	151.2	119.5	96.2	77.2	66.9	51.1	41.3	31.7	25.3	21.3	18.6	15.1	12.6	7.06
1.80V/cell	193.9	169.2	133.6	110.6	86.9	74.1	55.8	44.8	34.1	27.2	22.8	19.8	16.0	13.2	7.42
1.75V/cell	206.9	180.5	142.6	114.6	89.5	76.6	57.7	46.3	35.0	27.9	23.3	20.2	16.3	13.6	7.49
1.70V/cell	212.6	187.1	148.3	118.8	92.1	79.1	59.5	47.7	36.0	28.5	23.9	20.6	16.5	13.8	7.58
1.67V/cell	221.0	192.9	152.4	121.3	93.4	80.4	60.5	48.5	36.4	28.9	24.2	20.9	16.6	13.9	7.63
1.60V/cell	224.1	195.6	154.5	126.7	97.0	83.6	62.9	50.5	37.8	29.9	25.0	21.5	16.9	14.0	7.77

LPG SERIES-GEL BATTERY

LPG12-70H (12V70Ah)

LEOCH BATTERY

APPLICATIONS

- Telecommunications
- Solar system
- Wind power system
- Engine starting
- Wheelchair, Floor cleaning machines, Golf trolley, Boats

GENERAL FEATURES

- 12 years design life (25℃)
- Gelled electrolyte for superior thermal management, long float life
- Efficient gas recombination decreases gassing/water and extends battery life
- Robust design - resilient in harsh conditions
- Proof against deep discharge - greater long-term energy delivery and cycle life

STANDARDS

- IEC60896 Certified
- Classified as"Long Life" according to Eurobat
- UL,CE Approved
- Manufactured in Leoch®IATF16949, ISO 45001,ISO 9001 and ISO 14001 certified production facilities

Discharge Characteristics



Charging Characteristics



Cycle Life in Relation to DoD



Self Discharge Characteristics



Leoch International Technology Ltd.
www.leoch.com

Leoch Batteries Pte Ltd
www.leoch.sg

Leoch Battery Corporation
www.leochamericas.com

Leoch Europe S.A.
www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation.
© LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-LPG12-70H-PD-EN-V2.1-20250306