XP SERIES-ULTRA HIGH RATE

XP12-540 (12V540W)

LEOCH BATTERY





CHARACTERISTICS

Item		Specifications
Rated Voltage		12V
Nominal Rate (25℃)	W_{15},1.67V/cell	540W/cell
Nominal Capacity (25℃)	C_{20},1.80V/cell	155Ah
Dimension	Length	335mm (13.2inches)
	Width	172mm (6.77inches)
	Container Height	275mm (10.8inches)
	Total Height	278mm (10.9inches)
Approx Weight		42.4kg (93.5lbs)
Terminal		T8(M6)
Container Material		ABS (UL94 HB or V-0 optional)
Short-circuit current		2499A
Internal Resistance (25℃)		Approx 3.8 mΩ (Fully charged)
Operating Temp. Range	Discharge	-15~50℃ (5~122°F)
	Charge	-20~40℃ (-4~104°F)
	Storage	-15~40℃ (5~104°F)
Nominal Operating Temp. Range		25±3℃ (77±5°F)
Max.Charging Current (25℃)		0.25C
Charge voltage (25℃)	Float Charge	Equalization Charge
	2.25-2.30V/cell	2.30-2.40V/cell
Temp. Coeffcient	-3mV/cell/℃	-4mV/cell/℃
Effect of temp. to Capacity	40℃ (104°F)	106%
	25℃ (77°F)	100%
	0℃ (32°F)	86%
Self Discharge	≤3% per month at 25°C (77°F)	

DISCHARGE TABLE

Constant Current Discharge (Amperes) at 25°C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	282.7	229.7	197.9	173.4	139.3	106.0	87.0	51.5	37.2	29.6	24.6	21.4	17.1	14.3	7.57
1.80V/cell	327.4	254.0	218.0	192.0	151.7	114.1	92.1	54.0	38.8	30.7	25.5	22.1	17.6	14.7	7.75
1.75V/cell	381.3	284.1	241.7	207.9	162.8	121.1	97.3	56.3	40.1	31.5	26.1	22.6	17.9	15.0	7.93
1.70V/cell	425.9	312.2	265.5	225.9	174.3	127.9	102.0	58.2	41.2	32.3	26.7	23.0	18.3	15.3	8.06
1.67V/cell	466.9	344.0	289.1	240.4	181.8	133.3	105.6	60.1	42.4	33.1	27.3	23.5	18.7	15.5	8.15
1.60V/cell	502.7	372.2	305.0	253.4	191.1	138.9	109.5	61.7	43.2	34.0	28.0	24.2	19.1	15.9	8.36

Constant Power Discharge (Watts/cell) at 25°C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	537.7	441.9	383.5	339.5	273.0	209.1	172.5	102.8	74.4	59.5	49.8	43.5	34.9	29.5	15.6
1.80V/cell	615.4	484.6	418.6	373.2	295.0	223.2	181.3	106.8	77.1	61.2	51.1	44.4	35.6	30.0	15.9
1.75V/cell	710.1	534.9	459.8	400.9	314.2	235.1	190.2	110.7	79.2	62.5	52.0	45.2	36.1	30.4	16.2
1.70V/cell	785.4	582.5	500.2	432.4	334.1	246.5	197.9	113.6	80.8	63.8	53.0	45.8	36.7	30.9	16.4
1.67V/cell	852.0	635.1	540.1	456.6	346.4	255.5	203.8	116.8	82.8	65.0	53.9	46.6	37.2	31.2	16.5
1.60V/cell	898.8	672.8	559.7	471.1	356.4	261.2	207.5	117.7	82.9	65.5	54.3	47.1	37.5	31.3	16.6

XP SERIES-ULTRA HIGH RATE

XP12-540 (12V540W)

LEOCH BATTERY

APPLICATIONS

- UPS
- Hospitals and Testing Laboratories
- Emergency Power Supply
- Electric starting
- Telecommunications
- Data Centers

GENERAL FEATURES

- 12 years design life (25℃)
- Excellent high current performance - optimised for short discharge time
- Advanced AGM technology for superior high-rate power
- Long Life Alloy - minimizing grid growth, reducing gassing and extending battery life
- Epoxy-sealed posts eliminate leaks
- Optimal energy density - saves floor space

STANDARDS

- Compliance with IEC 60896 standards
- Classified as "Long Life" according to Eurobat
- CE,UL Approved
- Manufactured in Leoch®IATF 16949, ISO 45001,ISO 9001 and ISO 14001 certified production facilities

Discharge Characteristics



Charging Characteristics



Effects of Temperature on Capacity



Self Discharge Characteristics



Leoch International Technology Ltd.
www.leoch.com

Leoch Batteries Pte Ltd
www.leoch.sg

Leoch Battery Corporation
www.leochamericas.com

Leoch Europe S.A.
www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation.
© LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-XP12-540-PD-EN-V3.0-20250326