


CONVENTIONAL FLOODED MOTORCYCLE BATTERY

LB30CL-B (12V29Ah)




GENERAL FEATURES

- Low maintenance
- High performance and dry charged high quality and flooded battery
- Shipped in dry condition with a separated acid pack

CHARACTERISTICS

Item	Specifications	
Nominal Voltage	12V	
Nominal Capacity (10HR)	29Ah	
Cold Cranking Performance Amps@0°F (-18°C)	300A	
Dimension (±2mm)	Length	165mm (6.50inches)
	Width	130mm (5.12inches)
	Container Height	192mm (7.56inches)
	Total Height	192mm (7.56inches)
Battery (with acid)	Approx Weight	8.23kg (18.1lbs)
Electrolyte	Approx Weight	2.26kg (4.98lbs)
Terminal type	A	
Battery type	Conventional Flooded (High Performance) Series	
Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C ₁₀
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	16~24h
	Constant-Current Charge:	
	Charging current 0.1C ₁₀ , when charging voltage up to 15.60V, continue to charge 2h	
Floating Charge	Initial charging current	Unlimited
	Voltage	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.
www.leoch.com

Leoch Batteries Pte Ltd
www.leoch.sg

Leoch Battery Corporation
www.leochamericas.com

Leoch Europe S.A.
www.leoch.eu