LCP SERIES-PUNCH BATTERY

LCP12-26W (12V26W)

LEOCH BATTERY





CHARACTERISTICS

Item		Specifications
Rated Voltage		12V
Nominal Rate (25℃)	W_{15},1.67V/cell	26W/cell
Nominal Capacity (25℃)	C_{20},1.75V/cell	7Ah
Dimension	Length	151mm (5.94inches)
	Width	65mm (2.56inches)
	Container Height	93.5mm (3.68inches)
	Total Height	99.5mm (3.92inches)
Approx Weight		2.15kg (4.74lbs)
Terminal		T1/T2
Container Material		ABS (UL94 HB or V-0 optional)
Short-circuit current		196A
Internal Resistance (25℃)		Approx 29 mΩ (Fully charged)
Operating Temp. Range	Discharge	-15~50℃ (5~122°F)
	Charge	-20~40℃ (-4~104°F)
	Storage	-15~40℃ (5~104°F)
Nominal Operating Temp. Range		25±3℃ (77±5°F)
Max.Charging Current (25℃)		0.3C
Charge voltage (25℃)	Standby Use	Cycle Use
	2.25-2.30V/cell	2.35-2.45V/cell
Temp. Coeffcient	-3mV/cell/℃	-5mV/cell/℃
Effect of temp. to Capacity	40℃ (104°F)	103%
	25℃ (77°F)	100%
	0℃ (32°F)	86%
Self Discharge	≤3% per month at 25°C (77°F). LCP series batteries may be stored up to 6 months at 25°C (77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	

DISCHARGE TABLE

Constant Current Discharge (Amperes) at 25°C (77°F)																
F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	21.7	13.9	10.6	8.62	6.34	5.05	4.16	3.05	2.40	1.73	1.38	1.17	1.00	0.790	0.647	0.342
1.80V/cell	23.4	14.8	11.1	8.96	6.55	5.18	4.26	3.11	2.44	1.76	1.40	1.19	1.02	0.800	0.656	0.346
1.75V/cell	24.6	15.3	11.5	9.21	6.71	5.29	4.35	3.17	2.48	1.79	1.42	1.20	1.03	0.810	0.662	0.350
1.70V/cell	25.8	16.0	11.9	9.49	6.89	5.41	4.43	3.22	2.52	1.81	1.44	1.22	1.04	0.820	0.669	0.353
1.67V/cell	26.7	16.4	12.2	9.68	7.01	5.50	4.50	3.27	2.55	1.83	1.45	1.23	1.05	0.830	0.674	0.356
1.60V/cell	28.3	17.1	12.6	9.97	7.20	5.64	4.60	3.34	2.60	1.86	1.48	1.25	1.07	0.840	0.682	0.359
Constant Power Discharge (Watts/cell) at 25°C (77°F)																
F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	44.7	28.8	23.1	18.1	13.4	9.79	8.10	5.96	4.69	3.40	2.72	2.32	1.99	1.57	1.29	0.684
1.80V/cell	47.6	30.3	24.1	18.7	13.7	10.0	8.27	6.06	4.77	3.45	2.75	2.35	2.02	1.59	1.30	0.692
1.75V/cell	49.6	31.3	24.8	19.1	14.0	10.2	8.41	6.15	4.84	3.49	2.78	2.37	2.04	1.61	1.31	0.700
1.70V/cell	51.5	32.4	25.5	19.6	14.3	10.4	8.53	6.24	4.90	3.54	2.82	2.40	2.06	1.62	1.33	0.706
1.67V/cell	52.8	33.1	26.0	19.9	14.5	10.5	8.65	6.31	4.94	3.57	2.84	2.42	2.07	1.63	1.34	0.711
1.60V/cell	54.9	34.0	26.7	20.4	14.8	10.7	8.80	6.42	5.03	3.62	2.88	2.45	2.10	1.65	1.35	0.719

LCP SERIES-PUNCH BATTERY

LCP12-26W (12V26W)

LEOCH BATTERY

APPLICATIONS

- Uninterruptable Power Supply (UPS)
- Electric Power System (EPS)
- Emergency backup power supply
- Alarm and security system
- Communication power supply
- DC power supply
- Auto control system

GENERAL FEATURES

- 5 years design life (25℃)
- Lead calcium alloy, sealed design, no watering required
- Puncture resistant micro-porous glass mat separators extend life
- Automatic grid punch manufacturing process and unique technology optimizes power capacity,cell consistency, and long-term reliability and service life

STANDARDS

- Compliance with IEC 60896 standards, EU Battery Directive
- UL,CE Approved
- Manufactured in Leoch®IATF 16949, ISO 45001, ISO 9001 and ISO 14001 certified production facilities

Discharge Characteristics



Charging Characteristics



Effects of Temperature on Capacity



Self Discharge Characteristics



Leoch International Technology Ltd.
www.leoch.com

Leoch Batteries Pte Ltd
www.leoch.sg

Leoch Battery Corporation
www.leochamericas.com

Leoch Europe S.A.
www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation.
© LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-LCP12-26W-PD-EN-V1.0-20250716